



Axicon 6025-S Barcode Verifier



The Axicon 'S' Range -for enhanced accuracy

Product Summary

The Axicon 6025 - S verifier is designed for all barcodes where a 4, 5, 6, 10 or 20mil aperture is mandatory up to a maximum width of 68mm (2.6") including quiet zones. The simple-to-use design reduces user error and eliminates product damage whilst providing the highest level of accuracy achievable for verification.

Typical Application

Consumer level (Point of Sale) barcodes whether being verified on film, cartons, bags, cans, pots or jars plus all linear barcodes of a similar size.

Enhanced Accuracy and Improved Productivity

The "S" range of Axicon verifiers has a "Continuous Scan" feature. Just place the verifier over the barcode, press the trigger and slide the verifier over the code - in less than a second you can have results averaged up to 100 scans of the code at different points in the bar height.

Benefits

- ISO/ANSI Verification Standards
- Up to 100 Scans / per Second
- Ideal for GS1 Databar Stacked Codes
- Multi Language user Interface
- Ideal for Barcodes with Small Height
- USB2 Connectivity

ades

automatic data entry and
identification systems

ADES AG

Ruchstückstrasse 19
8306 Brüttsellen
Tel. +41 44 835 20 60
Fax. +41 44 835 20 69
www.ades.ch
info@ades.ch



Church Road
Weston on the Green,
Oxfordshire,
OX25 3QP, U.K.
Tel +44 (0)1869 351 155
email: sales@axicon.com
www.axicon.com

axicon

THE BARCODE EXPERTS



**Solution
Partner**

Axicon 6025-S Barcode Verifier



SOFTWARE SPECIFICATIONS

| | |
|---|--|
| Symbologies Verified: | GS1 SYMBOLOGIES: EAN-8, EAN-13 (with or without add-ons), ITF-14/Case Code, GS1-DataBar (all symbologies), GS1-128, UPC-A, UPC-E (with or without add-ons). OTHER SYMBOLOGIES: Code 39, Code 93, Code 128, Codabar, ITF, MSI Plessey, Pharmacode (Laetus: optional extra). |
| Application Standards: | AIAG, Belgian Pharmacode (MSI), Belgian Pharmacode (Unique), CIP39, Coupon Codes (UK, USA, Euro), Code Vignette, GS1 AI Check, HIBC, ISBN/ISSN, Italian Pharmacode (IMH), LPPR, M&S, PZN, SISAC, Variable Measure Codes (Branded, Instore, Australian). |
| Analysis Performed on Relevant Symbologies: | Full ISO/ANSI Parameter Analysis (Rmin, Rmax, Global Threshold, Symbol Contrast, Min Edge Contrast, Modulation, Defects, Decodability, Decode), Decodability per Symbol Character, Average Bar Gain, Check Digit Validation, Data Length, Nominal Bar Width Analysis (X Dimension), Print Contrast Measurement (PCS), Symol Structure including Parity, Subsets & Start/Stop Characters, Quiet Zone Validation, Wide to Narrow Ratio Display and Validation. |
| Diagnostics Windows: | Parameter Detail Results, Dimensional Analysis, Pass/Fail, Scan Reflectance Profile, Static Scan Reflectance, Summary, Traditional Results, Application Identifier Data Content Checker (for GS1-128, GS1-DataBar), Product-Look-Up. |
| Logging: | Scan Saving and Loading - stores complete details of scan file data. Allows for remote diagnostics and also for increased traceability. |
| Calibration Logging: | A record of date and time to show when the hardware has been calibrated is kept - vital for ISO 9000 records. |
| Configurable Options: | Audible Warnings, Calibration Expiry Warning, Changeable Pass / Fail and Warning Colours, Optional Check Digit Validation (Code 39, Codabar, ITF), File Saving, Multi-Scan Averaging, Pass Grade, Print Options, Window Sizes and Positions. |
| Error Messages: | Check Digit Error, Data Content Error, Incorrect Wide to Narrow Ratio, Print Quality Failure, Product Look-Up Error, Quiet Zone Error, Reference Decode Algorithm Error, Structure Error, X Dimension Range Checking. |
| Plugins Available: | Code 39 full ASCII, CSV File Saving, Gen Spec, Job Reference, Product Look-up, Text Look-up, Time Zone, UPC, User Data, User Name, (see also Application Standards). |
| Additional Software: | Pharmacode (Laetus) - Decode and Analysis of Laetus Pharmacode. ScanDB - Reporting Tool transferring data from saved scans into a .csv file. RepGen - Configurable report generation tool. |

HARDWARE SPECIFICATIONS

| | |
|----------------------|--|
| Dimensions: | 165 x 92 (50) x 128 mm (6.4" x 3.5" (2") x 5"), Scan Width - 68mm / 2.6" including quiet zones |
| Weight: | 273g (9.6oz) |
| Construction: | ABS plastic |
| Interface: | USB2 |
| Power Consumption: | Current draw 110mA - supplied from USB host. |
| Nominal Measuring: | 4mil, 5mil, 6mil, 10mil and 20mil. |
| Aperture: | The software automatically identifies the symbology/nominal bar size (X dimension) and adjusts the aperture size in order to comply with the symbology specifications and International Standards. |
| Wavelength of Light: | 660 nanometers |

GENERAL INFORMATION

| | |
|-----------------------|--|
| Print of Analysis: | A printed report can be produced on any connected printer. The report will be automatically resized to suit the output media. Printouts can be produced for the main verification information (including: Decoded Number, Time & Date, Number of Scans, Code Type, Average ISO/ANSI Grade, Average Bar Gain, Magnification, Check Character, Quiet Zone & Individual Parameters) Scan Reflectance Profiles, Dimensional Analysis, also for GS1-128 & GS1-DataBar Data Content information and Plugin Results. GS1 Verification Template supported. Customised reports available via RepGen and ScanDB utilities. |
| Standard Accessories: | Transit Case, Calibration Sheet, Start-up Guide, Software CD, Compliance Certificates. |
| System Requirements: | PC running Windows xp or later with a USB2 port available |
| Environmental: | Operating Temperature: 10° to 40° C |
| Storage Temperature: | -20° to 70° C |
| Relative Humidity: | 25% to 80% @ 40° C non-condensing |
| Warranty: | 2 years parts and labour - return to bench. |

All trademarks are acknowledged as belonging to their respective companies.
Due to Axicon's continuing product improvement programs, specifications and features herein are subject to change without notice.
Please note that not all features are available on Mac OS

axicon
THE BARCODE EXPERTS

Church Road,
Weston on the Green,
Oxfordshire, OX25 3QP, U.K.
Tel +44 (0)1869 351 155
email: sales@axicon.com
www.axicon.com