



Be unique Stylish and flawless POS printers



Chic

The CT-S251 is perfect for high class restaurants and boutiques where the environment requires a top class POS printer with eye-catching design. Choose between the white or black versions.

Fast

With its unique and stylish design, the two-inch CT-S251 POS printer is perfect for receipt or queue management systems. With a class-leading 300 mm/s print speed, front exit and compact size, the CT-S251 blends performance and poise.

CITIZEN CT-S251 POS

Applications

- Receipts
- Queue management
- Weigh scales
- Coupons
- Daily reports
- Hospitality



Well connected

Connectivity is key with the possibility for USB, Serial, MFi Bluetooth®, Ethernet and WiFi interfaces and toolkit support for iOS™, Android™ and Windows® operating systems. That creates ideal conditions for easy integration.





Easy to use

Thanks to the robust yet user friendly design, the CT-S251 has quick and efficient paper loading, preventing paper jams.



Specifications

Model	CT-S251	
Printing method	Line Thermal Dot Printing	
Printing width	54mm/432 dots	
Dot pitch	8 x 8 dots/mm (203 dpi x 203 dpi)	
Number of columns	Up to 36 digits (12 x 24: font A), Up to 48 digits (9 x 24: font B), Up to 54 digits (8 x 16: font C)	
Printing speed	Max. 300mm/sec., When greyscale printing: 130mm/sec	
Line spacing	4.23mm (1/6 inch); adjustable by user comand	
Barcode type	UPC-A, UPC-E, JAN / EAN-8, JAN / EAN-13, ITF, CODE39, CODE93, CODE128, CODABAR (NW-7), PDF417, QR Code, GS1 Databar.	
Emulation	ESC/POS™®	
Paper	Width	57.5 ± 0.5 mm
	Diameter	83mm or less
	Thickness	53µm to 85µm
	Recommended Paper	Mitsubishi Paper Mills P220AG normal type 65, HP220AB-1 highly conserved type 75, F230AA normal type 65, P220AB normal type 85, Oji Paper PD150R normal type 75, PD160R high storage type 65/75, Nippon Paper TF50KR-2Y high storage type 62, TR50KJ-R high-save type 63
Power adapter	37AD2 (AC Adapter)	
AC input voltage	AC 100 to 240V, 50/60 Hz, 150 VA	
DC operating voltage	24V DC ±7%, supplied by AC adapter	
Weight	1.20 Kg	
Dimension (W x D x H)	108 x 165 x 108 mm footprint. +5mm front lip	
Operating environment	+5 to +45°C, 10% - 90% RH, non condensing	
Storage environment	-20 to +60°C, 10% - 90% RH, non condensing	

All product names are trademarks of the respective manufacturers. ESC/POS™® are trademarks or registered trademarks of Seiko Epson Corporation. Bluetooth® is a registered trademark of the Bluetooth SIG and WiFi is the registered trademark of the Wi-Fi Alliance. Android™ is a trademark of Google Inc., IOS™ is a trademark of Cisco Systems. Windows® is either a registered trademark or trademark of Microsoft Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded.

CITIZEN CT-S251 POS

Features & Benefits

- Front Exit
- Fast 300 mm/sec
- 2-inch media: 57.5 ± 0.5 mm
- MFi / iOS™ Bluetooth® version
- WiFi and Ethernet versions
- ENERGY STAR® power supply
- Stylish black or white case
- Same height as cash drawers
- Cash drawer connection
- ESC/POS™® compatibility
- SDKs for iOS™, Android™, Windows®

